

# Gvision LCD Monitor J5PX Series

15-inch TFT Display with Touchscreen

## - Product Specification -

Configuration	J5PX-WO	
LCD Display	15" TFT active matrix panel	
Display Size (HxV mm)	304 x 228	
Pixel Pitch (HxV mm)	0.297 x 0.297	
Max. Resolution	XGA 1024x768	
Contrast Ratio	350:1 (typical)	
Brightness	250 cd/m <sup>2</sup> (typical)	
Response Time	30 ms	
Display Color	16M	
Viewing Angle	L/R	+70°~-70° (typical)
	U/D	+70°~-70° (typical)
PC Interface	Video	RGB analog 0.7V peak to peak
	Sync.	TTL positive or negative
Display Mode	VGA 720x400 (70 Hz)	
	VGA 640x480 (60/66/70/72/75 Hz)	
	SVGA 800x600 (60/70/72/75 Hz)	
	XGA 1024x768 (60/70/75 Hz)	
Signal Connector	D-sub 15 pin	
Front Control	Power on/off with LED, Menu, Select, Adjustment (+,-)	
OSD	Brightness, Contrast, Clock, Phase, Auto-tune, H-position, V-position,	
	R.G.B. color drive, OSD format, Volume	
Plug & Play	DDC1/2B compatible	
Speaker	1W/per channel driver	
Power	Embedded AC input power system, universal 90-264 Volts	
Operating Conditions	Temperature	0°C~40°C (32°F~104°F)
	Humidity	10%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C~60°C (-4°F~140°F)
	Humidity	10%-80% (no condensation)
Dimensions (HxDxW inches)	15.3 x 14.9 x 3.0 (without base)	
Weight (lbs)	11.4 (without base)	
Standard Features & Options	<b>Touch-ready monitor engineered for eash touch screen installation.</b>	
Certification	C-UL, FCC, TUV/GS, CE, MPR II, EPA, NUTEK, D, N, S, F, TCO (optional)	

\* Specifications are subject to change without notice.

*Catch the wave of the future - Now!*

**Gvision USA Inc.**

1582 Parkway Loop, Suite C, Tustin, CA 92780

