

# Gvision LCD Monitor Spring Ice Series

## - Product Specification -

Configuration		S5FX & S5HX
LCD Display		15" TFT active matrix panel
Display Size		304(H) x 228(V) mm
Pixel Pitch		0.297(H) x 0.297(V)mm
Max. Resolution		XGA 1024 x 768
Contrast Ratio		350:1 (max.) / 200:1(min.)
Brightnee		250 cd/m2 (max.)/200 cd/m2(min.)
Response Time		30 ms (min.)/50ms (max.)
Display Color		16M
Viewing Angle	L/R	+70°~-70°
	U/D	+70°~-50°
PC Interface	Video	RGB analog 0.7Vpeak to peak
	Sync.	TTL positive or negative
Display Mode		VGA 640X350 (70 Hz)
		VGA 720X400 (70 Hz)
		VGA 640X480 (60/72/75 Hz)
		SVGA 800x600 (56/60/72/75 Hz)
		Mac. 832 x 624 (75Hz)
Signal Connector		D-sub 15 pin
Front Control		Power on/off with LED, Menu, Select (Up, Down), Adjustment (+,-)
OSD		Brightness, Contrast, Clock, Phase, Auto-tune, Recall H-position, V-position, R.G.B. color drive, Audio volume
Plug & Play		DDC 1/2B compatible
Video-In (optional)		S & RCA connector (NTSC/PAL Auto-detect)
Touch panel (optional)		Capacitive / Resistive / Touch Pen Type with RS232 connector
Power		Imbedded AC input power system, universal 100-240 Volts
Operating Conditions	Temperature	5°C~35°C (41°F~95°F)
	Humidity	20%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C~60°C (-4°F~140°F)
	Humidity	10%-90% (no condensation)
Dimensions	Open Frame	400.6(H) x 311(W) x 57(D)mm
	Panel Mount	402.6(H) x 313(W) x 66.7(D)mm
Weight (lbs)	Open Frame	10.56 (net)
	Panel Mount	11.66 (net)

\* Specifications are subject to change without notice.

*Catch the wave of the future - Now!*

**Gvision USA Inc.**

1582 Parkway Loop, Suite C, Tustin, CA 92780

