



<b>RESOLUTION</b> 1080P FULL HD	<b>HDMI INPUT</b> 	<b>BNC CVBS IN/OUT</b> 	<b>VIEWING ANGLE</b> 178° / 178°	<b>BACKLIGHT</b> LED	<b>WARRANTY</b> 3 YEAR
------------------------------------	-----------------------	----------------------------	-------------------------------------	-------------------------	---------------------------

## FEATURES

- 24-Inch Screen Size
- 1920 x 1080 FHD Resolution
- Interface: HDMI / 2x HD Analogue In / 2x HD Analogue Out
- **TVI / CVI / AHD / CVBS** Auto Recognition
- Supports **5MP TVI / 4MP CVI / 5MP AHD**
- LED Backlight Unit
- Robust **Metal** and **Plastic** Housing
- **24/7 365** Operation Commercial CCTV Monitor
- **3-Year** Warranty

## SPECIFICATIONS

DISPLAY		C24BD-AU-400G
Screen Size		24 In
Resolution		1920 x 1080
Backlight		LED
Aspect Ratio		16 : 9
Viewing Angle		178° / 178°
Response Time		5ms
Brightness		250cd/m <sup>2</sup>
Contrast Ratio		1000 : 1
Color Depth		16.7M

INTERFACE		
<b>CVBS BNC In</b>		<b>2x HD Analogue (TVI/AHD/CVI)</b>
<b>CVBS BNC Out</b>		<b>2x HD Analogue (TVI/AHD/CVI)</b>
HDMI In		1
HD Analogue	TVI	720P@25/30fps, 1080P@25/30fps, 2560x1440@25/30fps, 5MP@20fps, 4MP@25fps, 3MP@18.75fps
	CVI	720P@25/30/50/60fps, 1080P@25/30fps, 2560x1440@25/30fps, 4MP@25fps
	AHD	720P@25/30fps, 1080P@25/30fps, 2560x1440@25/30fps, 5MP@20fps, 4MP@25fps

FEATURES	
OSD Language	English, Spanish, Italian, German, French, Polish, Russian, Dutch, Danish
Auto Adjustment	Yes
OSD Control	Yes

CABINET	
Color	Black

POWER	
Consumption	< 25W
Electrical Ratings	12V DC / 5A (AC 100V ~ 240V, 50/60Hz)

TEMPERATURE	
Operating	32° F ~ 104° F (0° C ~ 40° C)
Storage	14° F ~ 140° F (-10° C ~ 60° C)

DIMENSIONS (WxHxD)	
Inch w/ Stand (in)	21.31 x 15.39 x 5.78
Millimeter w/ Stand (mm)	541.37 x 391.07 x 147.00

WEIGHT	
Net Weight	13.88 lbs (6.3kg)

VESA™	
Mount Size (mm)	100 x 100

COMPLIANT	
Certificate	FCC-DOC, CE, ROHS

PACKAGE OF CONTENTS	
Accessories	Power cord, Adapter, Stand, User's guide, HDMI cable

*Specifications subject to change without any notice*

# C24BD-AU-400G

Gvision's Full HD CCTV security monitors are specifically engineered for continuous operation throughout the year. These monitors boast support for HDMI, BNC CVBS HD analog inputs and outputs, as well as automatic recognition of BNC AHD/TVI/CVI. The C24BD security CCTV is capable of accommodating 5MP TVI, 4MP CVI, and 5MP AHD HD analogue formats.

## DIMENSIONS

Unit: Inch

