

360° (Horizontal) x 180° (Vertical) Field of View AI-Friendly 4K Video Patrol Camera



FEATURES

- 360° (Horizontal)/ 180° (Vertical)/ F2.2 Optical Features
- PoE 802.3at Class 4 Power
- Ethernet 10/100/1000 via 1x RJ45 Interface
- Real-time in-chip stitching technology for 5.7K/4K videos
- Zero distortion, AI-friendly
- Perfect for various applications, including smart factories, smart cities, smart tourism, and smart retail, to improve operational efficiency
- Superior immersive spatial experience without blind spots
- Shock Resistance, Vibration Resistance, Electrical Safety
- EMI/EMS Regulation (CE, FCC, EMC, ISED, AS/NZS), NDAA and TAA-Compliant
- IoT integration capable

GU1FA7201

SPECIFICATIONS	
Interface	Ethernet 10/100/1000 via RJ45 xl
Power	PoE 802.3at Class 4
Power Consumption	11.5W
Video Output	640x320@30fps 1920x960@30fps 1920x1080@30fps 3840x1920@30fps 2880x5760@15fps H.264 in RTP/RTSP streaming
Control	DHCP/DNS/NTP/HTTP/HTTPS/IPV4/TCP/UDP/ RTP/RTSP/RTMP/ONVIF (Profile S)
Optical Features	360° (Horizontal)/ 180° (Vertical)/ F2.2
Audio	Microphone xl
Features	1/4" camera screw hole PMS 877 C Aluminum / Anodized ,IEC60529_IP66 Humidity (IEC 60068-2-78) Salt Test (MIL-810F section 509.4), Solar Testing(IEC-60068), Thermal Shock(MIL-810), IoT integration capable
Temperatures	-10° C to 50°C operating
Humidity	5% to 90% RH
Shock Resistance	Drop Testing(IEC-60950-01), 6 feet(1.83 meters), concrete floor,Top and bottom face, No camera lens side
Vibration Resistance	Vibration(IEC 60068-2-64), Random vibration along three perpendicular axes for 2 hours with 0.41G RMS acceleration level over 3 to 500Hz
Electrical Safety	CB: IEC 62368-1 : 2018 ED.3 EU / CE: EN 62368-1 ED.2 New Zealand/ Australia: AS/NZS 62368-1 ED.2 test Taiwan / safety: CNS 15598-1
EMI/EMS Regulation, Compliant	Taiwan / EMC: BSMI(CNS15936) EU / CE: EN 55032 / EN 55035, Class A USA / FCC: 47 CFR Part15, Subpart B, Class A Canada / ISED: ICES-003, Issue 7, Class A AS/NZS: CISPR 32, Class A NDAA, TAA
Dimensions	68 x 68 x 200mm (Not including accessory cap, lens, PoE Cable)
Weight	2.27 Lbs (1.03 Kg)

***Specifications may change without any notice*

30398 Esperanza,
Rancho Santa Margarita, CA 92688

888-651-9688 / 949-586-3338

sales@gvision-usa.com
<https://www.gvision-usa.com>

