



FEATURES

- 24-Inch Screen Size / 1920 x 1080 Full HD Resolution
 - Embedded Linux / Support **PoE Power & Data**
 - Support **Max. 5MP IP Camera / H.264, H.265** Compression Format
 - **Graphical and Text** Interfaces (GUI)
 - Interface: **HDMI / DVI / VGA / RJ45 / Audio / USB2.0** Ports
 - Supports **Max. 16CH** Network Cameras via **HUB / Switch****
 - **ONVIF** Compliance, **Real-Time** Streaming Protocol
 - **Metal** Chassis / **TAA** Compliance
 - **3-Year** Warranty
- **Hub/Switch PoE required up to 40W.*


1080P
FULL HD

SPECIFICATIONS

DISPLAY	IP24BD-OK-400T
Screen Size	24 In
Resolution	1920 x 1080
Display Area (mm)	527.04(H) x 294.16(V)
Pixel Pitch (mm)	0.276.7(H) x 0.276.7(V)
Backlight	LED Direct
Aspect Ratio	16 : 9
Viewing Angle	178° / 178°
Response Time	5ms
Brightness	250cd/m ²
Contrast Ratio	3000 : 1
Color Depth	16.7M
INTERFACE	
RJ45	1x PoE & Network Port
HDMI	1
DVI-D	1
VGA (15Pin D-Sub)	1
USB	2x USB 2.0
Audio In (R/L)	2x (RCA)
Earphone Out	1x Phone jack ,3.5μ
AUDIO	
Speaker	2x built-in speaker (2 Watt)
VIDEO	
IP Video Support	16x (2592x1944) / 8x (2592x1944) / 4x (2592x1944)
CABINET	
Material	Metal
POWER	
POE Input DC Range	36~57VDC (Complies w/ IEEE802.3at IEEE802.3at/4-Pairs)
Power Input (<i>If no PoE Input</i>)	100-240V 50/60Hz, Adapter DC 12V/5A
Power Consumption	Approx. 27Watt
TEMPERATURE	
Operating	32° F ~ 122° F (0° C ~ 50° C)
Storage	-4° F ~ 140° F (-20° C ~ 60° C)
DIMENSIONS (WxHxD)	
Inch (in)	22.67 x 13.69 x 2.53
Millimeter (mm)	575.9 x 347.8 x 64.5
WEIGHT	
Net Weight	12.56 Lbs (5.7 Kg)
VESA™	
Mount Size (mm)	100 x 100
PACKAGE CONTENTS	
Accessories	1.5m (5ft) HDMI Cable

Specifications subject to change without any notice

TAA
COMPLIANT



IP24BD-OK-400T

Gvision's IP Series monitors are PoE Power and Data devices with embedded Linux which is a powerful tool that enables viewing of live or recorded video feeds from network-enabled surveillance cameras.

DIMENSIONS

Unit: Inch

