




FEATURES

- 21.5-Inch Screen Size
- 1920 x 1080 Full HD Screen Resolution
- Zero Pressure Touch Activation
- LED Backlight Unit
- 10-Points Projective Capacitance PCAP Touch
- IP65 Frpnt Protection
- Video Signal: VGA (15 Pin D-Sub) / DVI
- Zero Bezel Touch Screen
- Free Portrait / Landscape Directions
- Design to Operate 24 / 7 / 365
- 3-Year Warranty



SPECIFICATIONS

DISPLAY	R22ZD-OB-45P0
Screen Size	21.5 In
Resolution	1920 x 1080
Backlight	LED
Aspect Ratio	16 : 9
Viewing Angle	170° / 160°
Brightness	250cd/m ²
Contrast Ratio	1000 : 1
Color Depth	16.7 M
Display Area (H x V)	476.64 x 268.11 mm
INTERFACE	
DVI	1
VGA (15 Pin D-Sub)	1
TOUCH TECHNOLOGY	
Protection Glass	2mm strengthen glass
Type	10-Points Projective Capacitance PCAP Touch
Support OS	Windows / Linux
FEATURE	
Privacy Filter	Option
Touch Frame	IP65
CABINET	
Material	Metal
POWER	
Consumption	< 22W
Electrical Ratings	DC 12V (AC 100V ~ 240V, 50/60Hz)
TEMPERATURE	
Operating	32° F ~ 104° F (0° C ~ 40° C)
Storage	-4° F ~ 140° F (-20° C ~ 60° C)
Humidity	20% ~ 80%
DIMENSIONS (WxHxD)	
Inch (in)	21.5 x 13.3 x 1.8
Millimeter (mm)	547.6 x 339.6 x 47.0
WEIGHT	
Net Weight	13.2 lbs (6kg)
VESA™	
Mount Size (mm)	100 x 100

Specifications subject to change without any notice

R22ZD-OB-45P0

Gvision's line of rear mount projected capacitive displays are purpose built for system builders who require a rugged and durable touch screen solution that can easily be integrated into any embedded application. It is completely sealed to protect against the elements, which means it can be used either inside or out, and in high-traffic public facing applications.

DIMENSION

Unit: Inch

