

S28AG

Ultra Wide LCD Displays

Features:

- Multi language OSD
- Portrait & Landscape supported
- Analog & Digital interface for plug and play convenience
- Support remote control function by RS232
- Multiple sizes available - 20", 28", 29", 37", and 38"
- 3 year warranty



Specifications

Part Number	S28AG
Display Size	28 in
Display Area	27.5 x 5 in (698.5 x 127 mm)
Panel Brightness	800 nits
Response Time	5 ms Typical (Tr + Tf)
Power Consumption	32W MAX; Standby ≤ 0.5W
VESA Mount	100 x 100 mm
Dimensions (W x H x D)	29 x 6.5 x 1.7 in (736x 165.1 x 43.2 mm)
Weight	6.8 lbs (3 kg)
Contrast Ratio	1000:1
Video Inputs	HDMI/ DVI-D/ VGA
Backlight	LED
Native Resolution	1920 x 360
Aspect Ratio	32:9
Viewing Angle	178°H / 178°V
Input Power	12VDC ± 5% (Adapter Input AC 100V ~ 240V, 50/60Hz)
MTBF	50,000 hrs
Temperature	Operating: 32°F ~ 104°F (0°C ~ 40°C) Storage: 14°F ~ 140°F (-10°C ~ 60°C)
Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
Enclosure Material	Metal Enclosure
Included Accessories	AC Adapter, VGA Cable

Mechanical Drawing

